

M52015-WH
M52015S-WH

OP AIR-PRO® OXYGEN
RESPIRATORY PROTECTION MASK FFP2 NR D
Personal Protective Equipment, Category III

FEATURES & BENEFITS

- Filtering half mask, efficiency class FFP2 NR D developed to protect against solid and liquid aerosols
- Ultrasonic welding
- M52015S items are individually packed in a polybag

Recommended use :

- Use in dusty environment
- To prevent against risky infectious diseases (According to national recommendations)
- Using: 8 H



PRODUCT DETAILS

Product name: **KOLMI - Op-Air Pro® Oxygen – Mask FFP2 NR D**
 Product type: Single use, non-sterile
 Inner/Outer layer: Spunbond 100% polypropylene
 Filter: Meltblown 100% polypropylene
 Nosepiece: Polypropylene and iron
 Color : White
 Origin : France



EN 149:2001+A1:2009

Test	Required level	Laboratory	Report number	Date of Report	Average value
Paraffin Oil penetration	< 6 % after 120mg exposure	APAVE	20.1742	01/12/2020	Compliant
NaCl penetration	< 6 % after 120mg exposure				Compliant
Facial leakage	≤ 11 % for at least 46 results over 50 ≤ 8% for at least 8 arithmetic means over 10				Compliant
Air permeability inhalation 30 l/min	≤ 0,7 mbars				Compliant
Air permeability inhalation 95 l/min	≤ 2,4 mbars				Compliant
Air permeability exhalation 160 l/min	≤ 3 mbars				Compliant
Carbon dioxide content	< 1,0 %				Compliant
Flammability	Must not burn or continue to burn for more than 5 seconds after the withdrawal of the flame				Compliant

Protection (D) : protection against solid and liquid aerosols, combined with resistance higher to clogging tested with dolomite dust

Annual observation according to module D - Reg (UE) 2016/425 done by APAVE

CERTIFICATION & STANDARDS

Meet the requirements of Regulation (EU) 2016/425 on personal protective equipment.
Comply with the applicable harmonized standards EN 149:2001+A1:2009.
Manufactured under ISO 13485 and ISO 9001 certified systems.

PRECAUTIONS FOR USE

The device should only be used on intact skin.
Their re-use or prolonged use can produce infection or cross-contamination.
After use, comply with the national regulations in force for the disposal of the device.

STORAGE

Normal conditions of conservation and storage: must not be exposed to humidity and sun, must be stored at a temperature between 5°C and 40°C.
Product life: 5 years.

LOGISTICAL INFORMATION



Outer case specifications

Item	Size mm	Gross weight kg	QTY/pallet
M52015-WH M52015S-WH	560 x 260 x 270	To be confirmed	36 boxes (6 layers of 6 boxes)

Inner case specifications

Size mm	QTY
255 x 110 x 133	10 boxes of 50 pieces

M52015S-WH items are individually packed in a polybag.

Codes EAN

Article	Carton	Boîte distributrice
M52015-WH	3 662 036 018 670	3 662 036 018 663
M52015S-WH	3 662 036 018 694	3 662 036 018 687